© Illumino Ignis Ltd. 2024. All Rights Reserved



13A Key Switch - DP Neon Surface Mounted

Absolute Essentials - Keyswitches

Part No. TC0139

Product Details

The surface mounted 13A Key Switch connection unit has a steel face plate and is suitable for domestic and commercial installations with the reassurance of BS 1363-4 certification.

Product Specifications	
Box Quantity	1
Total Weight	165g
Plate Size	Single
Width	80mm
Height	80mm
Depth	41.5mm
Minimum Wall Box Depth	40mm
Contact Gap Minimum	3mm
Gangs	1
Associated Standards	BS 1363-4
Rated Voltage	220-250V
Rated Current	13A
Maximum Load	13A
Frequency	50-60Hz
Face Plate Material	Steel
Insert	White Insert
Surround	White Surround
Face Plate Material	Steel
Switched Poles	Double
IP Rating	IP2XD
Ambient Operating Temp.	-5 to 40°C
Max. Installation Altitude	2,000m
Terminal Capacity	3 x 2.5mm ² 2 x 4mm ² Multi-strand 1 x 6mm ²
Earth Terminal Capacity	6 x 1mm ² 5 x 1.5mm ² 2 x 4mm ² Multi-strand 1 x 6mm ²
BS EN ISO Standard(s)	BS 1363-4



Key Features

- Surface mounted
- White insert
- Surface mounted
- Complete with back box
- 2 x M3.5 fixing screws
- Double pole key switch fused spur with neon
- Key included
- CE marked
- Internal Use Only
- Must be earthed

ISSUE 01



1





T: 0203 00 44 855 E: sales@illuminoignis.co.uk www.**illuminoignis.co.**uk

Illumino Ignis Ltd, Ignis House, Imperial Way, Eagle Business Park, Yaxley, Cambridgeshire, PE7 3GP