

177401

ZP755R-2R room sounder C/W cover

General

The ZP755R-2R is a RED, addressable loop powered room sounder or us on ZP fire alarm systems. The ZP755R-2R combines a detector base and audible sounder in a single stylish moulding.

The ZP755R-2R is developed for applications in individual rooms, sleeping accommodation or small compartments where it is impractical or unnecessary for the sounder and detector to be combined. Installed directly onto a ZP7 wiring loop - the ZP755R-2R enables the system designer to offer a complete addressable system on a single pair of wires. Installation costs are greatly reduced, whilst system integrity, sounder options and programmed alarm organisation are significantly increased. Time on site is further reduced as the moulding plugs directly into a first fix base – eliminating the need for any wiring directly to the device.

Advanced acoustic design

High efficiency acoustic design and a low energy, sound gun transducer, enable combinations of up to 60 sensors and 60 sounders to be connected to a 1 km loop of 1.5 mm² cable. In systems where loop lengths or current requirements are excessive, the ZP755R-2R sounders can be locally powered from an external power supply.

Output Test and Tone Selection

The ZP755 range of notification devices features a unique self-test facility which is automatically activated during routine sounder testing. A built in microphone circuit measures sound output level and automatically signals the sounder address and location to the control panel, should the output test fail.

Continuous, intermittent and two-tone outputs are available from which any combination can be chosen to provide alert and evacuate for two stage alarms. Sound types comply with most international codes (e.g. BS 5839 Part 1 recommended frequencies). The ZP755R-2R features a sound output of up to 90dBA and a volume control for areas where a reduced sound output is required.



Details

- Powered directly from the ZP loop
- Up to 60 detectors and 60 sounders directly on the loop wiring
- Plug in base – no direct wiring connections
- High efficiency sound gun transducer
- Wide range of international sound types and frequencies
- EN54:3 Approved and CPR certified

177401

ZP755R-2R room sounder C/W cover

Technical specifications

General

Compatibility	All ZP7 addressable systems
Addressing method	DIP Switches
Monitoring	Device removal, Device type, Open circuit, Short circuit, Sound output
Addressing method	7 way dipswitch

Electrical

Operating voltage	Loop powered: 19.5 to 20.5 V Externally powered: 18 to 30 VDC
-------------------	--

Sounder

Output level	<70 dB(A) (tone dependant)
Selectable tones	Sound types: User configurable

Physical

Physical dimensions	127 x 69 mm (Ø x H)
Net weight	205 g
Colour	Red
Mounting type	Surface mount
Material	Moulded thermoplastic
Mounting	Surface mount with plug in base - SPB-2R (White)

Environmental

Operating temperature	-10 to +60°C
Storage temperature	-20 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP21C

Regulatory

Certification	CPR, EN54-3
---------------	-------------

Loop current

Quiescent (when loop powered)	820 µA
Active (when loop powered)	4.5 mA
Quiescent (when externally powered)	470 µA
Active (when externally powered)	500 µA

Devices per loop (max.)

60 (1 km loop of 1.5 mm ² cable, 50 m to first device)

Wiring

2 core loop

Compatible products

Category	Reference	Description
Notification device	70802	Red Cap for ZP755B Series Notification Devices
Notification device	SPB-2R	Plug-in Base, RED



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 4 June 2024 - 11:19