

VESTA-270N-720P

VST-892-IL-SF1 (lithium)



Indoor PIRCAM 720P Detector



- PIRCAM Vesta indoor detector
- PIR coverage of 10 meters, 90°
- Sensitivity configurable from APP
- Optics 102°, IR illumination of 7 meters
- Resolution 720P
- Antimasking and anti-pet 20~50 kg
- Powered by 2 lithium batteries
- EN50131 Grade 2 certified
- BOGP compatible.



Reference / Model

VESTA-270N-720P / VST-892-IL-SF1 (lithium)

Detection range of 10 meters, 90°.

Advanced dynamic speed adjustment algorithms to maintain an image transfer rate depending on signal quality

2.3 ~ 2.5 meters installation height

Anti-pet up to 20 kg / 50 cm

Blind spot free detection

Four alarm image processing options: 1280x720@3ips, 640x480@3ips, 320x240@3ips and 320x240@6ips

Image delivery on demand

Anti-masking function

Infrared nighttime illumination capability, up to 7 meters range

F1 technology accelerates transmission speed and increases communication range

Periodic monitoring signals

Tampering protection

VESTA-270N-720P

VST-892-IL-SF1 (lithium)



Indoor PIRCAM 720P Detector

Reference / Model

VESTA-270N-720P / VST-892-IL-SF1 (lithium)

Low battery detection

Suitable for security and home automation

Compatible with Climax F1 gateways / control panels and **VESTA-030** repeater (RP-29-F1)

RF frequency: 868MHz

Communication range 400 ~ 900 meters in open field

10k, 20k, 30k, 50k, 80k data rate

Detection range: 10 meters, 90°, installed at a height of 2.3 ~ 2.5 meters

VGA CMOS sensor

Horizontal viewing angle: 102°.

Resolution: 640 x 480, 320 x 240

Infrared illumination up to 7 meters

Power supply: 2 lithium batteries

Battery life up to 4 years

Operating temperature -10°C ~ +45°C (-10°C ~ +45°C)

Relative humidity up to 85% (non-condensing)

Dimensions: 63 (W) x 123 (H) x 45 mm

EN50131 Grade 2 certified

BOGP compatible