

Manual 'No Break' Call Point, surface

Part No. **BF370S**



Overview

- Certified to EN54 Parts 11 (LPCB) and 13 (BSI).
- Smooth-action resettable element mimics the feel of breaking glass.
- Supplied with a red back box, reset key and 'Not in Use' label.
- Red LED 'alarm ring' illuminates call point face upon activation.
- Photoluminescent operating window remains visible for up to 5 minutes.
- Note an additional BF370SFP red flush mounting plate is required if you wish to flush mount the BF370S.
- IP66 weatherproof version (order code BF370S/W) also available.



More Information

Technical Specifications

Approvals/certifications	Certified to EN54 Parts 11 by the LPCB and 13 by the BSI.
Supply/operating voltage	4.5-30Vdc
Product dimensions (mm)	87 W x 88 H x D 62mm (includes back box).
Construction & finish	Red ABS.
IP Rating	IP42.



Weight TBC.
Properties Supplied with a 470Ω & 680Ω resistor (value selected by wiring connection).
Operating conditions/temperature -30°C to +70°C.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom