

ActiV Conventional Hi-Output 100dB(A) Wall Sounder (deep base) Part No. BF430C/CC/DR



Overview

- Third-party certified to EN54-3 (Sounders).
- Impressive 100dB(A) sound output @ 1m.
- Includes 31 selectable primary tones and an optional secondary tone.
- Two volume levels (high and low)
- Alarm Current at 30Vdc = 5.5mA.
- Alarm Current at 18Vdc = 3.8mA.
- IP33C rated.
- Manufactured in the UK by C-TEC.

×××

More Information

Technical Specifications

Approvals/certifications

Certified to EN54-3 by the LPCB.

rippi o (dio) ooi dii oddiolio	
Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Can be used in covered outdoor areas.
VAD category & coverage	N/A.
Flash rate & colour	N/A.
Supply/operating voltage	18 to 30V DC.
Nominal SPL (Sound Pressure Level)	100dB(A).



 T
 01942 322744
 E
 sales@c-tec.co.uk

 F
 01942 829867
 W
 www.c-tec.com

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



Alarm current Product dimensions (mm) IP Rating Weight Operating conditions/temperature

At 30Vdc: 5.5mA; At 18Vdc: 3.8mA. 114mm diameter x 132mm deep. IP33C (Type B). 315g. -10ºC to +55ºC. Max. 95% RH (Non-condensing).



T 01942 322744 E sales@c-tec.co.uk **F** 01942 829867 W www.c-tec.com

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



